


BELT CLEANING BRUSH PAD



The Belt Cleaning Brush Pad offers a unique solution to cleaning belts with a profiled surface including those with sidewalls and cleats.

FEATURES:

- Works very well on cleaning products that are profiled and require deburring
- A flat pad with 2" fingers which can be adhered to a shaft and mounted in the pulley area
- Back surface already prepared for easy installation
- Works in belt cleaning applications such as chip belts in pulp and paper and cleaning cement blocks.
- Can be mounted on any existing pulley

| PROPERTIES | | | |
|---------------------|--------------------------|----------|-----------|
| Elastomer | NR 70% SBR 30% | | |
| Tensile Strength | 19.0 Mpa | 2755 psi | DIN 53504 |
| Elongation at Break | 550% | | DIN 53504 |
| Density | 1.10 g / cm ³ | | DIN 35050 |
| Hardness | 65 Shore A | | DIN 53505 |

| | Width | | Length | | Height | |
|--------------|-------|-----|--------|-----|--------|----|
| PRODUCT CODE | in | mm | in | mm | in | mm |
| CCR-RBP-001 | 11.75 | 300 | 29.3 | 747 | 2 | 50 |



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011